

AMENDMENTS TO THE CLAIMS

1. (Canceled).
2. (Currently amended) A motorhome, comprising:
 - a chassis having at least two parallel interconnected chassis members having top, bottom, and side surfaces;
 - a floor section that is mounted to the top surface of the chassis members;
 - a storage floor positioned below the bottom surface of the chassis members;~~and~~
 - a plurality of vertically arranged structural members that interconnect the storage floor to the floor section, wherein each of the vertically arranged structural members defines a plane that is substantially perpendicular to the chassis members such that the floor section, the storage floor, and the plurality of vertically arranged structural members define one or more spaces that are at least partially enclosed, and wherein each of the vertically arranged structural members attaches to the side surface of at least one of the chassis members thereby providing a three-dimensional space frame structure about at least one of the chassis members~~;~~

wherein the plurality of vertically arranged structural members includes at least one bulkhead panel that extends laterally beyond the at least two chassis members, wherein the at least one bulkhead panel comprises a rectangular shaped panel having top and bottom edges, and wherein the rectangular shaped panel defines a cutout having side edges that attach to the outermost surfaces of the at least two chassis members, and wherein the top edge attaches to the floor section and the bottom edge attaches to the storage floor.
3. (Canceled).
4. (Canceled).
5. (Previously presented) The motorhome of Claim 2, wherein the plurality of vertically arranged structural members includes at least one bulkhead panel that extends laterally outward from one of the outermost chassis member.
6. (Previously presented) The motorhome of Claim 5, wherein the at least one bulkhead panel comprises a rectangular shaped panel having top, side, and bottom edges, such

Appl. No. : **10/776,025**
Filed : **February 10, 2004**

that the top edge attaches to the floor section, the side edge attaches to the outermost surface of one of the chassis members, and the bottom edge attaches to the storage floor.

7. (New) The motorhome of Claim 2, wherein the cutout is defined along the top edge of the rectangular shaped panel.

8. (New) The motorhome of Claim 2, wherein the cutout is defined along the bottom edge of the rectangular shaped panel.

9. (New) The motorhome of Claim 2, wherein the side edges of the cutout define folds that are generally perpendicular to the plane of the bulkhead panel, such that the folds facilitate attachment of the side edges to the outermost surfaces of the at least two chassis members.